

Bulbflattstål AH-36
EN 10067:1996
Lengdetoleranse -0/+30mm
Kontrollsertifikat EN 10204 3.2
DNV - Inspeksjonsorgan



Varenr	Dimensjon	Lengder	Kg/mtr	Kg/stk
12000	80 x 6	6 m	4,95	29,7
12003	100 x 6	6 m	6,2	37,2
12006	100 x 7	6 m	7	42
12009	100 x 8	6 m	7,8	46,8
12012	120 x 6	6 m	7,42	44,52
12015	120 x 7	6 m	8,42	50,52
12018	120 x 8	6 m	9,35	56,1
12021	140 x 7	6 m	9,93	59,58
12024	140 x 8	6 m	11,01	66,06
12027	160 x 7	12 m	11,63	139,56
12030	160 x 8	12 m	12,95	155,4
12033	160 x 9	12 m	14,28	171,36
12036	180 x 8	12 m	15,1	181,2
12039	200 x 9	12 m	18,87	226,44
12042	200 x 10	12 m	20,5	246
12045	220 x 10	12 m	23,26	279,12
12048	240 x 10	12 m	25,91	310,92
12054	260 x 12	12 m	33,05	396,6

Bulbflattstål DH-36
EN 10067:1996
Lengdetoleranse -0/+30mm
Kontrollsertifikat EN 10204 3.2
DNV eller Loyds Register - Inspeksjonsorgan



Varenr	Dimensjon	Lengder	Kg/mtr	Kg/stk
12028	160 x 7	12 m	11,63	139,56
12040	200 x 9	12 m	18,87	226,44