

**Flattstål S355J2+AR**

EN 10025-2/2019 CE

Lengdetoleranse -0, +100mm

Toleranser iht EN 10058

Sertifikat iht EN 10204:2004 / 3.1

The logo for BAUTA metal, featuring the word "BAUTA" in a large, bold, white sans-serif font with a teal vertical bar to the left of the 'A'. Below "BAUTA" is the word "metal" in a smaller, teal, lowercase sans-serif font.

Varenr	Dimensjon	Lengder	Kg/mtr	Kg/stk
1155	30 x 6mm	6	1,44	8,64
1154	30 x 8 mm	6	1,92	11,52
1156	40 x 5 mm	6	1,6	9,6
1153	40 x 6 mm	6	1,92	11,52
1157	50 x 5 mm	6	2	12
1158	50 x 6 mm	6	2,4	14,4
1159	50 x 8 mm	6	3,2	19,2
1160	100 x 5 mm	6	4	24
1163	100 x 8 mm	6	6,41	38,46
1161	100 x 10 mm	6	8	48
1162	150 x 15 mm	6	18	108

**Vinkelstål S355J2+AR**

EN 10025-2/2019 CE

Lengdetoleranse -0, +100mm

Toleranser iht EN 10056

Sertifikat iht EN 10204:2004 / 3.1

The logo for BAUTA metal, featuring the word "BAUTA" in a large, bold, white sans-serif font with a teal vertical bar to the left of the 'A'. Below "BAUTA" is the word "metal" in a smaller, teal, lowercase sans-serif font.

Varenr	Dimensjon	Lengder	Kg/mtr	Kg/stk
1164	40 x 40 x 4,00 mm	6,1	2,47	15,07
1165	50 x 50 x 5,00 mm	6,1	3,85	23,49
1166	60 x 60 x 6,00 mm	6,1	5,53	33,73

**HEB S355J2**

EN 10025-2/2019

Lengdetoleranse -0, +100mm

Toleranser iht EN 10034

Sertifikat iht EN 10204:2004 / 3.1

**BAUTA.**  
metal

Varenr	Dimensjon	Lengder	Kg/mtr	Kg/stk
1060	<b>HEB 100</b>	<b>12</b>	20,8	249,6
1061	<b>HEB 120</b>	<b>12</b>	27,2	326,4
1062	<b>HEB 140</b>	<b>12</b>	34,4	412,8
1063	<b>HEB 160</b>	<b>12</b>	43,5	522
1064	<b>HEB 180</b>	<b>12</b>	52,2	626,4
1065	<b>HEB 200</b>	<b>12</b>	62,5	750
1066	<b>HEB 200</b>	<b>15</b>	62,5	937,5
1067	<b>HEB 220</b>	<b>12</b>	72,9	874,8
1068	<b>HEB 220</b>	<b>15</b>	72,9	1093,5
1069	<b>HEB 240</b>	<b>12</b>	84,9	1018,8
1070	<b>HEB 260</b>	<b>12</b>	94,9	1138,8
1071	<b>HEB 280</b>	<b>12</b>	105,1	1261,2
1072	<b>HEB 300</b>	<b>12</b>	119,3	1431,6
1073	<b>HEB 300</b>	<b>15</b>	119,3	1789,5
1074	<b>HEB 320</b>	<b>12</b>	129,5	1554
1075	<b>HEB 340</b>	<b>12</b>	136,7	1640,4
1076	<b>HEB 360</b>	<b>12</b>	144,8	1737,6
1077	<b>HEB 360</b>	<b>15</b>	144,8	2172
1078	<b>HEB 400</b>	<b>12</b>	158,1	1897,2
1079	<b>HEB 400</b>	<b>15</b>	158,1	2371,5
1080	<b>HEB 500</b>	<b>15</b>	190,7	2860,5

**IPE S355J2**

EN 10025-2/2019

Lengdetoleranse -0, +100mm

Toleranser iht EN 10034

Sertifikat iht EN 10204:2004 / 3.1

**BAUTA.**  
metal

Varenr	Dimensjon	Lengder	Kg/mtr	Kg/stk
1001	IPE 100	12	8,4	100,8
1002	IPE 140	12	13,3	159,6
1003	IPE 180	12	19,2	230,4
1004	IPE 200	12	22,9	274,8
1005	IPE 200	15	22,9	343,5
1006	IPE 220	12	26,7	320,4
1007	IPE 240	12	31,3	375,6
1008	IPE 300	12	43	516
1009	IPE 330	12	50,1	601,2
1010	IPE 360	12	58,2	698,4
1011	IPE 400	12	67,6	811,2
1012	IPE 500	12	92,5	1110

**UPN S355J2**

EN 10025-2/2019

Lengdetoleranse -0, +100mm

Toleranser iht EN 10034

Sertifikat iht EN 10204:2004 / 3.1

**BAUTA.**  
metal

Varenr	Dimensjon	Lengder	Kg/mtr	Kg/stk
1020	UPN 160	12	19,4	232,8
1021	UPN 180	12	22,7	272,4
1022	UPN 200	12	26,1	313,2
1023	UPN 220	12	30,3	363,6

**UPE S355J2**

EN 10025-2/2019

Lengdetoleranse -0, +100mm

Toleranser iht EN 10034

Sertifikat iht EN 10204:2004 / 3.1

The logo for BAUTA metal, featuring the word "BAUTA" in large white capital letters with a teal vertical bar to the left of the "A", and the word "metal" in smaller teal lowercase letters below it, all on a black rectangular background.

Varenr	Dimensjon	Lengder	Kg/mtr	Kg/stk
1030	<b>UPE 140</b>	<b>12</b>	14,9	178,8
1031	<b>UPE 180</b>	<b>12</b>	20,3	243,6